

Resilient Tyres

SUPER SOLID



IRC's resilients

are designed as per the latest European Construction guidelines to give you the best performance in every application.

If trailer, forklift or any other application our patterns will match every known application to give the best possible performance for every of your equipment.

2 or 3 stage IRC cordbase resilient tyres

specially designed for the best possible economical use of resilient tyres. The properties are matching all expectations of regular application's.

our resilient's are made out of natural rubber compounds to give you the maximum properties of high quality moulded rubber products.



Sizes		Nominal Dimension			Load Capacity in kg					
Tyre Size	Rim Size	Weight in kg	OD (Inch)	WIDTH (Inch)	Forklifttrucks		Other Vehicles			
					25 km/h		6 km/h	10 km/h	25 km/h	Static
					Load Wheel	Steer Wheel				
3.00 - 4	2.10 - 4	3.80	9.88	3.2	260	195	260	235	195	290
	2.50C - 4	4.00	9.9	3.2						
4.00 - 4	2.10 - 4	6.50	12.0	4.5	530	410	530	485	410	600
	2.50C - 4	6.70	12.0	4.5						
4.00 - 8	2.50C - 4	9.80	15.7	4.5	950	730	950	860	730	1050
	3.00D - 8	10.00	15.7	4.5						
	3.25I - 8	11.50	15.7	4.5						
	3.75 - 8	11.90	15.7	4.5	1005	770	1005	910	770	1100
5.00 - 8	3.00D - 8	16.00	17.7	4.5	1410	1090	1410	1250	1090	1600
	3.25I - 8	16.50	17.7	4.5						
	3.75 - 8	17.00	17.7	4.5						
15 x 4 1/2 - 8	3.00D - 8	10.50	14.5	4.5	1040	800	1040	940	800	1200
	3.25I - 8	11.30	14.5	4.5						
16 x 6 - 8	4.33R - 8	15.50	16.0	6.0	1490	1150	1490	1350	1150	1730
18 x 7 - 8	4.33R - 8	19.50	17.6	6.1	2140	1650	2140	1940	1650	2450
18 x 9 - 8	7.00E - 8	31.00	17.8	8.9	2530	1950	2530	2300	1950	2940
6.00 - 9	4.00E - 9	25.00	20.2	5.3	1880	1450	1880	1710	1450	2190
21 x 8 - 9	6.00E - 9	34.00	20.4	7.2	2750	2100	2750	2500	2100	3200
	7.00E - 9	36.00	20.4	7.2	2890	2220	2890	2620	2220	3350
6.50 - 10	5.00F - 10	34.30	22.3	6.8	2340	1800	2340	2120	1800	2700
	5.50F - 10	35.60	22.3	6.8						
23 x 9 - 10	6.50F - 10	43.00	22.6	7.9	3440	2650	3440	3120	2650	4000
200 / 50 - 10	6.50F - 10	25.00	18.0	7.9	2470	1900	2470	2240	1900	2870
7.00 - 12	5.00S - 12	45.20	25.4	6.9	2920	2240	2920	2645	2240	3380
27 x 10 - 12	8.00G - 12	70.00	26.0	9.5	3900	3000	3900	3540	3000	4530
7.00 - 15	5.50 - 15	51.00	28.5	7.2	3540	2720	3540	3215	2720	4115
	6.00 - 15	53.00	28.5	7.2						
7.50 - 15	5.50 15	70.30	29.3	7.9						
	6.00 - 15	72.60	29.3	7.9	3900	3000	3900	3540	3000	4530
	6.50 - 15	75.00	29.3	7.9						
8.25 - 15	6.00 - 15	80.00	31.5	8.0						
	6.50 - 15	85.00	31.5	8.0	4600	3540	4600	4175	3540	5345
28 x 9 - 15	6.50 - 15	53.00	27.2	8.6	4750	3650	4750	4300	3650	5510
	7.00 - 15	55.00	27.2	8.6	3770	2900	3770	3125	2650	4380
28 x 12.5 - 15	9.75 - 15	87.00	28.0	13.0	5520	4250	5525	4575	3875	6420
250 - 15	7.00 - 15	67.00	27.9	8.4	4745	3650	4745	4200	3570	5510
	7.50 - 15	69.00	27.9	8.4						
300 - 15	8.00 - 15	105.00	31.9	10.2	5850	4500	5850	5210	4410	6795
355 / 65 - 15	9.75 - 15	125.00	31.8	12.2	7800	6000	7000	6430	5450	9060
7.50 - 20	6.00 - 20	82.00	34.1	7.7	3900	3250	3900	3520	3200	4910
	6.50 - 20	84.00	34.1	7.7						
8.25 - 20	6.50 - 20	111.00	38.4	9.4	4400	3650	4400	4005	3675	5510
	7.00 - 20	114.00	38.4	9.4						
	7.50 - 20	117.00	38.4	9.4						
9.00 - 20	6.50 - 20	116.00	38.4	9.5	5400	4500	5400	4850	4450	6795
	7.00 - 20	118.00	38.4	9.5						
	7.50 - 20	119.00	38.4	9.5						
10.00 - 20	6.50 - 20	143.00	39.4	10.2						
	7.00 - 20	148.00	39.4	10.2	5840	4875	5840	5315	4865	7360
	7.50 - 20	150.00	39.4	10.2	6000	5000	6000	5450	5000	7550
	8.00 - 20	155.00	39.4	10.2						
12.00 - 20	8.00 - 20	195.00	41.0	11.0						
	8.50 - 20	203.00	41.0	11.0	7560	6300	7560	6815	6250	9500
	10.00 - 20	211.00	41.0	11.0	8520	7100	8520	7740	7100	10720
12.00 - 24	8.00 - 24	210.00	46.9	11.3	8040	6700	8040	7250	6650	10100
	8.50 - 24	230.00	46.9	11.3						
	10.00 - 24	290.00	46.9	12.8						

