

W-1

S型块状系列花纹

适用于重型自卸汽车、铲运机和装载机在多种条件下作业，具有广泛的通用性，特殊的胎面设计和胶料配方及强力胎体结构设计，使其具有优良的耐热、耐磨耗性能和优良的牵引性能，是各种矿山、建筑工地广泛采用的经久耐用的轮胎

S BLOCK PATTERN TYRE SERIES

Suitable to heavy dump trucks, scrapers and loaders operating under many conditions, with extensively universal characteristic, the combination of special tread design provides excellent heat and wear resistances, excellent traction, the tyre is a kind of durable tyre extensively suitable to various mining areas and buliding sites



花纹编号 PATTERN	轮胎规格 TYRE SIZE	层级 PLY RATING	国际花纹代号 INTERNATIONAL TREAD PATTERN	花纹深度 TREAD DEPTH (mm)	标准轮辋 STANDARD RIM	新胎充气后主要尺寸(mm) INFLATED SIZE OF NEW TYRE		最大负荷 (KG) MAXIMUM LOAD	相应气压 (KPA) RELATIVE PRESSURE	内胎 TT/TL
						断面宽 SECTION WIDTH ± 3.5%	外直径 OVERALL DIAMETER ± 1.5%			
W-1	14.00-24	24	L-3/E-3	25.5	10.0	348	1370	4580/6030	630	TT/TL
		28						5040/6640	740	
		32						6420/7150	840	
		36						7800/9660	840	
		40						9120/10100	840	
	15.5-25	16	L-3/E-3	24.5	12.00/1.3	383	1275	2980/6340	320/530	TT/TL
		20						3500/6900	390/530	
	16.00-25	28	L-3/E-3	28.5	11.25/2.0	410	1517	5590/7360	560	TT/TL
		32						6890/8250	580	
		36						8190/9020	700	
		40						9490/10900	740	
	17.5-25	16	L-3/E-3	25.5	14.00/1.5	435	1344	3600/7020	320/490	TT/TL
		20						4050/7620	390/530	
		24						4500/8100	460/590	
	18.00-25	32	L-3/E-3	31.5	13.00/2.5	472	1640	7220/9150	560	TT/TL
		36						7740/10190	630	
		40						8250/11000	840	
	20.5-25	16	L-3/E-3	30	17.00/2.0	512	1487	4280/7730	280/350	TT/TL
		20						7730/9070	350/460	
		24						8100/9700	460/530	
	23.5-25	16	L-3/E-3	31.5	19.50/2.5	580	1600	5170/9470	250/320	TT/TL
		20						5530/10630	280/390	
		24						5850/11000	475	
		28						6400/11800	630	
40		11800						745		
26.5-25	24	L-3/E-3	35	22.00/3.0	667	1750	8070/14000	390/490	TL	
	28						8700/15500	350/460		
	32						9900/17000	350/460		
29.5-25	28	L-3/E-3	38	25.00/3.5	745	1875	8850/17500	425	TL	
	34						10500/18500	475		
29.5-29	28	L-3/E-3	38	25.00/3.5	714	1970	10050/19400	460	TL	
	34						11000/21200	525		