

# W-2

## 耐磨型块状系列花纹

适用于铲运机和重型自卸车，在矿区、隧道和采石场及建筑工地等较差路面作业时，具有良好的抗切割，耐磨耗性能，特殊的肩部加强设计，使其具有较高的保护性及耐高温性，并具有卓越的抓地性能。

## ANTI-WEARING BLOCK PATTERN TYRE SERIES

Suitable to scrapers and heavy dump trucks operating on relatively poor road in areas like mining area,tunnel quarry,construction site,etc.with good cutting and wear resistance,special shoulder reinforcing design provides relatively high production and high temperature resistance,also eximious griping ground capability.



花纹编号 PATTERN	轮胎规格 TIRE SIZE	层级 PLY RATING	国际花纹代号 INTERNATIONAL TREAD PATTERN	花纹深度 TREAD DEPTH (mm)	标准轮辋 STANDARD RIM	新胎充气后主要尺寸(mm) INFLATED SIZE OF NEW TIRE		最大负荷 (KG) MAXIMUM LOAD	相应气压 (KPA) RELATIVE PRESSURE	内胎 TT/TL
						断面宽 SECTION WIDTH ± 3.5%	外直径 OVERALL DIAMETER ± 1.5%			
W-2	15.5-25	16	L-3/E-3	24.5	12.00/1.3	395	1275	2980/6340	320/530	TT/TL
		20						3500/6900	390/530	
	16.00-25	28	L-3/E-3	28.5	11.25/2.0	430	1490	5590/7360	560	TT/TL
		32						6890/8250	580	
		36						8190/9020	700	
		40						9490/10900	740	
	17.5-25	16	L-3/E-3	25.5	14.00/1.5	445	1350	3600/7020	320/490	TT/TL
		20						4050/7620	390/530	
		24						4500/8100	460/590	
	18.00-25	32	L-3/E-3	31.5	13.00/2.5	495	1615	7220/9150	560	TT/TL
		36						7740/10190	630	
		40						8250/11000	840	
		16						4080/7730	280/350	
	20.5-25	20	L-3/E-3	30	17.00/2.0	520	1490	7730/9070	350/460	TT/TL
		24						8100/9700	460/530	
		16						5170/9470	250/320	
	23.5-25	20	L-3/E-3	31.5	19.50/2.5	595	1615	5530/10630	280/390	TT/TL
		24						5850/11000	475	
		28						6400/11800	630	
		40						11800	740	
24		8850/14000						390/490		
26.5-25	28	L-3/E-3	35	22.00/3.0	675	1750	9400/15500	350/460	TL	
	32						10200/17000	350/460		
	28						8070/17500	425		
29.5-25	34	L-3/E-3	38	25.00/3.5	750	1875	9900/18500	475	TL	
	28						10050/19400	460		
29.5-29	34	L-3/E-3	38	25.00/3.5	750	1875	11000/21200	525	TL	