



## 通用型块状花纹

适用于铲运机，叉车，在港口、机场、工厂、仓库等环境下作业，具有良好的抗切割，耐磨损性能，宽厚的胎面花纹，提供了良好的接地及牵引性能，自洁性好，寿命长。

## GENERAL PURPOSE BLOCK PATTERN TYRE SERIES

Suitable to scrapers and forklifts operating in areas like port, air port, factory and warehouse sites etc., with good cutting and wear resistances, wide and thick tread pattern provides good ground contact and traction, self-cleaning, long service life.

# W-9A



# W-9B



花纹编号 PATTERN	轮胎规格 TIRE SIZE	层级 PLY RATING	标准轮辋 STANDARD RIM	新胎充气后主要尺寸(MM) INFLATED SIZE OF NEW TIRE		最大负荷 (KG) MAXIMUM LOAD	相应气压 (KPA) RELATIVE PRESSURE	内胎 TT/TL
				断面宽 SECTION WIDTH ±3.5%	外直径 OVERALL DIAMETER ±1.5%			
W-9A	5.00-8	8	3.50D	137	470	1210	800	TT
	6.00-9	10	4.00E	160	540	1625	850	TT
	7.00-9	10	5.00S	190	590	2145	850	TT
	6.50-10	10	5.00F	175	590	1775	775	TT
	7.00-12	12	5.00S	190	676	2555	850	TT
	8.25-12	12	7.00	235	696	2850	790	TT
	7.50-15	12	6.00	215	808	2650	790	TT
	8.15-15	12	7.00	215	704	3230	840	TT
W-9B	8.25-15	12	6.50	235	840	3545	720	TT
		14				3700	800	
	9.00-20	18	7.00	262	1022	2700	740	TT
	10.00-20	18	7.50	280	1060	3000	740	TT
	12.00-20	20	8.50	320	1130	3700	740	TT